

8.7/15KV Heat Shrinkable Straight Through Joint

Usage:

3.6/6(7.2)KV	6/10(12)KV	8.7/15(17.5)KV
XLPE to XLPE cable	XLPE to XLPE cable	XLPE to XLPE cable
PILC to PILC cable	PILC to PILC cable	PILC to PILC cable
XLPE to PILC cable	XLPE to PILC cable	XLPE to PILC cable

Components:

Stress control tube, Insulation/conductive tube, Inner-sleeve, Protective sleeve, Copper screen mesh Semi-conductive tape, J-30 Tape, PVC tape, Sealing mastic, Stress relieving mastic, Silicon grease. Earth braid, Cleaning tissue, Copper binding wire, Soldering tin, Soldering unguent, Cotton strap. Gloves, Abrasive strap(Oil-resistant tube, Oil-resistant tri-way breakout, Oil-resistant protective sleeve,. Semi-conductive tube Metal case. Ending sleeve, Ending metal jacket, Heat shrinkable ring, Plastic triangle-support, Oil-resistant mastic, F4 tape, Insulation tape, Oil grease for PILC cable)



Order Reference

Type/Order No	Name	Cable range(mm ²)
8.7/15(17.5)KV RSJY/1-1	Straight through joint for 8.7/15(17.5)KV XLPE cable (1 core)	25-50
8.7/15(17.5)KV RSJY/1-2		70-120
8.7/15(17.5)KV RSJY/1-3		150-240
8.7/15(17.5)KV RSJY/1-4		300-400
8.7/15(17.5)KV RSJY/1-5		500
8.7/15(17.5)KV RSJY/1-6		630
8.7/15(17.5)KV RSJY/1-7		800
8.7/15(17.5)KV RSJY/3-1	Straight through joint for 8.7/15(17.5)KV XLPE cable (3 cores)	25-50
8.7/15(17.5)KV RSJY/3-2		70-120
8.7/15(17.5)KV RSJY/3-3		150-240
8.7/15(17.5)KV RSJY/3-4		300-400
8.7/15(17.5)KV RSJYZ/3-1	XLPE-PILC transition joint for 8.7/15(17.5)KV XLPE cable (3 cores)	25-50
8.7/15(17.5)KV RSJYZ/3-2		70-120
8.7/15(17.5)KV RSJYZ/3-3		150-240
8.7/15(17.5)KV RSJYZ/3-4		300-400
8.7/15(17.5)KV RSJZ/3-1	Straight though joint for 8.7/15(17.5)KV PILC cable (3 cores)	25-50
8.7/15(17.5)KV RSJZ/3-2		70-120
8.7/15(17.5)KV RSJZ/3-3		150-240
8.7/15(17.5)KV RSJZ/3-4		300-400

Aluminum or Copper Ferrule and Amour continue components can be supplied as specification.