

8.7/15(17.5)KV Heat Shrinkable Indoor/Outdoor Termination

Usage:

- ◆ 3.6/6(7.2)KV XLPE cable, PILC cable
- ◆ 6/10(12)KV XLPE cable ,PILC cable
- ◆ 8.7/15(17.5)KV XLPE cable, PILC cable

Components:

Stress control tubes, insulation 3-way,insulation tubes, Sealing tubes, Filler mastic

Stress relieving mastic, Sealing mastic, Silicone grease, Phase-color tubes, Rain shed, Clearing tissue

Soldering tin, Soldering unguent, Earth braid, Copper binding wire, Abrasive paper, Gloves (Oil-resistant tubing, Oil-resistant 3-way breakout, Oil-resistant mastic, Plastic triangle-support Heat shrinkable ring(oil-resistant),F4 Tape, Oil-cup, Oil grease, Metal clip for PILC cable)



Order Reference

Type/Order No	Name	Cable Range(mm ²)
8.7/15(17.5)KV RSNY/1-1	Indoor termination for 8.7/15(17.5)KV XLPE cable (1core)	25-50
8.7/15(17.5)KV RSNY/1-2		70-120
8.7/15(17.5)KV RSNY/1-3		150-240
8.7/15(17.5)KV RSNY/1-4		300-400
8.7/15(17.5)KV RSNY/1-5		500
8.7/15(17.5)KV RSNY/1-6		630
8.7/15(17.5)KV RSNY/1-7		800
8.7/15(17.5)KV RSWY/1-1	Outdoor termination for 8.7/15(17.5)KV XLPE cable(1 core)	25-50
8.7/15(17.5)KV RSWY/1-2		70-120
8.7/15(17.5)KV RSWY/1-3		150-240
8.7/15(17.5)KV RSWY/1-4		300-400
8.7/15(17.5)KV RSWY/1-5		500
8.7/15(17.5)KV RSWY/1-6		630
8.7/15(17.5)KV RSWY/1-7		800
8.7/15(17.5)KV RSNY/3-1	Indoor termination for 8.7/15(17.5)KV XLPE cable(3 cores)	25-50
8.7/15(17.5)KV RSNY/3-2		70-120
8.7/15(17.5)KV RSNY/3-3		150-240
8.7/15(17.5)KV RSNY/3-4		300-400
8.7/15(17.5)KV RSWY/3-1	Outdoor termination for 8.7/15(17.5)KV XLPE cable(3 cored)	25-50
8.7/15(17.5)KV RSWY/3-2		70-120
8.7/15(17.5)KV RSWY/3-3		150-240
8.7/15(17.5)KV RSWY/3-4		300-400
8.7/15(17.5)KV RSNZ/3-1	Indoor termination for 8.7/15KV(17.5)KV PILC cable(3 cores)	25-50
8.7/15(17.5)KV RSNZ/3-2		70-120
8.7/15(17.5)KV RSNZ/3-3		150-240
8.7/15(17.5)KV RSNZ/3-4		300-400
8.7/15(17.5)KV RSWZ/3-1	Outdoor termination for 8.7/15(17.5)KV PILC cable(3 cores)	25-50
8.7/15(17.5)KV RSWZ/3-2		70-120
8.7/15(17.5)KV RSWZ/3-3		150-240
8.7/15(17.5)KV RSWZ/3-4		300-400

Aluminum or Copper Lug, Support insulator, Tee bracket can be supplied as specification.