


18/30(36)KV Heat Shrinkable Indoor/Outdoor Termination

Usage :XLPE cable, PILC cable

Components:

Stress-control tube, Insulating tube, Insulation 3-way breakout, Sealing tube, Rain shed, Phase color tube, Sealing mastic ,Stress-relieving mastic, Filler mastic, Silicon grease, J-30 self-adhesive tape, Cleaning tissue, Copper binding wire, Copper braid, Soldering tin, Soldering unguent, Cotton strap, Gloves, Abrasive strap.

(Oil-resistant tubing, Oil-resistant 3-way breakout, Oil-resistant mastic, Plastic triangle-support Heat shrinkable ring(oil-resistant), F4 tape, Oil-cup, Oil-grease, Metal clip for PILC cable)



Order Reference:

Type/Order No	Name	Cable range(mm ²)
18/30(36)KV RSNY/1-1	Indoor termination for 18/30(36)KV XLPE cable(1 core)	25-120
18/30(36)KV RSNY/1-2		150-240
18/30(36)KV RSNY/1-3		300
18/30(36)KV RSWY/1-1	Outdoor termination for 18/30(36)KV XLPE cable(1 core)	25-120
18/30(36)KV RSWY/1-2		150-240
18/30(36)KV RSWY/1-3		300
18/30(36)KV RSNY/3-1	Indoor termination for 18/30(36)KV XLPE cable(3 cores)	25-120
18/30(36)KV RSNY/3-2		150-240
18/30(36)KV RSNWY/3-1	Outdoor termination for 18/30(36)KV XLPE cable(s cores)	25-120
18/30(36)KV RSNWY/3-2		150-240
18/30(36)KV RSNZ/1-1	Indoor termination for 18/30(36)KV PILC cable(1 core)	25-50
18/30(36)KV RSNZ/1-2		70-120
18/30(36)KV RSNZ/1-3		150-240
18/30(36)KV RSWZ/1-1	Outdoor termination for 18/30(36)KV PILC cable(1 core)	25-50
18/30(36)KV RSWZ/1-2		70-120
18/30(36)KV RSWZ/1-3		150-240
18/30(36)KV RSNZ/3-1	Indoor termination for 18/30(36)KV PILC cable(3 cores)	25-50
18/30(36)KV RSNZ/3-2		70-120
18/30(36)KV RSNZ/3-3		150-240
18/30(36)KV RSWZ/3-1	Outdoor termination for 18/30(36)KV PILC cable(3 cores)	25-50
18/30(36)KV RSWZ/3-2		70-120
18/30(36)KV RSWZ/3-3		150-240

Aluminum or Copper Lug, Support insulator, Tee bracket can be supplied as specification.