



CYG-HWT
Heavy Wall Heat Shrink Tubing Heat Shrinkable Tubing Single Wall
CYG-HWTA
Heavy wall Heat Shrinkable Tubing Adhesive-coated, Dual Wall

Applications

- ◆Non Flame Retardant
- ◆Single Wall,3:1

- ◆Flat in reel/Oval in piece
- ◆RoHS Compliant

Features

- ◆Excellent insulating abilities
- ◆Resistant to Impact and abrasion
- ◆Bigger Shrinkable Ratio for you easier and faster installation
- ◆Continuous Working Temperature -55°C to 110°C
- ◆Convenient and free lengths cutting

Technical Data :

Property	Test Method	Typical Data
Tensile strength	ASTM D2671	≥14MPa
Elongation at break	ASTM D2671	≥400%
Elongation at break after aging	ASTM D2671/150°C,168hrs	≥300%
Density	ASTM D792	1.05g/cm ³
Eccentricity	ASTM D2671	<30%
Longitudinal shrinkage	UL224	0 to-10%
Dielectric strength	IEC243	≥20KV/mm
Volume resistivity	IEC93	≥10 ¹⁴ Ω.cm
Copper stability	ASTM D2671	Pass
Water absorption	ISO 62/23°C,14 days	<0.15%

Dimensions :

Ordering Ref.	Wall thickness Recovered (mm, Min.)	Shape/ Style	Standard Length (mm)	Ordering Units (pcs/Carton)	Package Dimensions (cm)
CYG-HWTA-9/3	1.8	O	1220	500	36*36*126
CYG-HWTA-13/4	2.4	O	1220	400	36*36*126

CYG-HWTA-22/6	2.7	O	1220	125	36*36*126
CYG-HWTA-33/8	3.2	O	1220	100	36*36*126
CYG-HWTA-40/12	4.1	O	1220	60	36*36*126
CYG-HWTA-55/16	4.1	O	1220	40	36*36*126
CYG-HWTA-75/22	4.1	O	1220	30	36*36*126
CYG-HWTA-85/25	4.3	O	1220	20	36*36*126
CYG-HWTA-95/30	4.3	O	1220	20	36*36*126
CYG-HWTA-115/34	4.3	O	1220	18	36*36*126
CYG-HWTA-130/36	4.3	—	1220	30	36*36*126
CYG-HWTA-160/50	4.3	—	1220	14	36*36*126
CYG-HWTA-175/50	4.3	—	1220	14	36*36*126
CYG-HWTA-205/60	4.3	—	1220	12	36*36*126

◆The dimensions of CYG-HWT as same as CYG-HWTA

