

0.6/1KV Heat Shrinkable Termination and Straight Through Joint

Test item:

- ◆ Insulation Resistance Test
- ◆ AV Voltage Withstand test at 3.5KV for 5min
- ◆ Impulse Voltage Withstand Test 8KV(10+ve&10-ve)
- ◆ Load Cycling Test at 95°C
- ◆ Insulation Resistance Test
- ◆ Impulse Voltage Withstand Test 8KV(10+ve&10-ve)
- ◆ DC Voltage Withstand Test at 15KV for 5min



Order Reference

Type/Order No	Name	Cable range(mm ²)
1KVRST-2/1	Termination for 1KV 2 cores cable	10-16
1KVRST-2/2		25-50
1KVRST-2/3		70-120
1KVRST-2/4		150-240
1KVRST-3/1	Termination for 1KV 3 cores cable	25-50
1KVRST-3/2		70-120
1KVRST-3/3		150-240
1KVRST-3/4		300
1KVRST-4/1	Termination for 1KV 4 cores cable	25-50
1KVRST-4/2		70-120
1KVRST-4/3		150-240
1KVRST-4/4		300
1KVRST-5/1	Termination for 1KV 5 core cable	25-50
1KVRST-5/2		70-120
1KVRST-5/3		150-240
1KVRST-5/4		300
1KVRSJ-2/1	Straight through joint for 1KV 2 cores cable	10-16
1KVRSJ-2/2		25-50
1KVRSJ-2/3		70-120
1KVRSJ-2/4		150-240
1KVRSJ-3/1	Straight through joint for 1KV 3 cores cable	25-50
1KVRSJ-3/2		70-120
1KVRSJ-3/3		150-240
1KVRSJ-3/4		300
1KVRSJ-4/1	Straight through joint for 1KV 4 cores cable	25-50
1KVRSJ-4/2		70-120
1KVRSJ-4/3		150-240
1KVRSJ-4/4		300
1KVRSJ-5/1	Straight through joint for 1KV 5 cores cable	25-50
1KVRSJ-5/2		70-120
1KVRSJ-5/3		150-240
1KVRSJ-5/4		300