

8.7/15KV Heat Shrinkable Straight Through Joint

Usage:

3.6/6(7.2)KV	6/10(12)KV	8.7/15(17.5)KV
XLPE to XLPE cable	XLPE to XLPE cable	XLPE to XLPE cable
PILC to PILC cable	PILC to PILC cable	PILC to PILC cable
XLPE to PILC cable	XLPE to PILC cable	XLPE to PILC cable

Components:

Stress control tube, Insulation/conductive tube, Inner-sleeve, Protective sleeve, Copper screen mesh Semi-conductive tape, J-30 Tape, PVC tape, Sealing mastic, Stress relieving mastic, Silicon grease. Earth braid, Cleaning tissue, Copper binding wire, Soldering tin, Soldering unguent, Cotton strap. Gloves, Abrasive strap(Oil-resistant tube, Oil-resistant tri-way breakout, Oil-resistant protective sleeve, Semi-conductive tube Metal case. Ending sleeve, Ending metal jacket, Heat shrinkable ring, Plastic triangle-support, Oil-resistant mastic, F4 tape, Insulation tape, Oil grease for PILC cable)



Order Reference

Type/Order No	Name	Cable range(mm ²)
8.7/15(17.5)KV RSJY/1-1	Straight through joint for 8.7/15(17.5)KV XLPE cable (1 core)	25-50
8.7/15(17.5)KV RSJY/1-2		70-120
8.7/15(17.5)KV RSJY/1-3		150-240
8.7/15(17.5)KV RSJY/1-4		300-400
8.7/15(17.5)KV RSJY/1-5		500
8.7/15(17.5)KV RSJY/1-6		630
8.7/15(17.5)KV RSJY/1-7		800
8.7/15(17.5)KV RSJY/3-1	Straight through joint for 8.7/15(17.5)KV XLPE cable (3 cores)	25-50
8.7/15(17.5)KV RSJY/3-2		70-120
8.7/15(17.5)KV RSJY/3-3		150-240
8.7/15(17.5)KV RSJY/3-4		300-400
8.7/15(17.5)KV RSJYZ/3-1	XLPE-PILC transition joint for 8.7/15(17.5)KV XLPE cable (3 cores)	25-50
8.7/15(17.5)KV RSJYZ/3-2		70-120
8.7/15(17.5)KV RSJYZ/3-3		150-240
8.7/15(17.5)KV RSJYZ/3-4		300-400
8.7/15(17.5)KV RSJZ/3-1	Straight though joint for 8.7/15(17.5)KV PILC cable (3 cores)	25-50
8.7/15(17.5)KV RSJZ/3-2		70-120
8.7/15(17.5)KV RSJZ/3-3		150-240
8.7/15(17.5)KV RSJZ/3-4		300-400

Aluminum or Copper Ferrule and Amour continue components can be supplied as specification.

8.7/15(17.5)KV Heat Shrinkable Indoor/Outdoor Termination

Usage:

- ◆ 3.6/6(7.2)KV XLPE cable, PILC cable
- ◆ 6/10(12)KV XLPE cable ,PILC cable
- ◆ 8.7/15(17.5)KV XLPE cable, PILC cable



Components:

Stress control tubes, insulation 3-way,insulation tubes, Sealing tubes, Filler mastic

Stress relieving mastic, Sealing mastic, Silicone grease, Phase-color tubes, Rain shed, Clearing tissue

Soldering tin, Soldering unguent, Earth braid, Copper binding wire, Abrasive paper, Gloves (Oil-resistant tubing, Oil-resistant 3-way breakout, Oil-resistant mastic, Plastic triangle-support Heat shrinkable ring(oil-resistant),F4 Tape, Oil-cup, Oil grease, Metal clip for PILC cable)

Order Reference

Type/Order No	Name	Cable Range(mm ²)	
8.7/15(17.5)KV RSNY/1-1	Indoor termination for	25-50	
8.7/15(17.5)KV RSNY/1-2	8.7/15(17.5)KV XLPE cable (1core)	70-120	
8.7/15(17.5)KV RSNY/1-3		150-240	
8.7/15(17.5)KV RSNY/1-4		300-400	
8.7/15(17.5)KV RSNY/1-5		500	
8.7/15(17.5)KV RSNY/1-6		630	
8.7/15(17.5)KV RSNY/1-7		800	
8.7/15(17.5)KV RSWY/1-1		Outdoor termination for 8.7/15(17.5)KV XLPE cable(1 core)	25-50
8.7/15(17.5)KV RSWY/1-2	8.7/15(17.5)KV XLPE cable(1 core)	70-120	
8.7/15(17.5)KV RSWY/1-3		150-240	
8.7/15(17.5)KV RSWY/1-4		300-400	
8.7/15(17.5)KV RSWY/1-5		500	
8.7/15(17.5)KV RSWY/1-6		630	
8.7/15(17.5)KV RSWY/1-7		800	
8.7/15(17.5)KV RSNY/3-1		Indoor termination for 8.7/15(17.5)KV XLPE cable(3 cores)	25-50
8.7/15(17.5)KV RSNY/3-2	8.7/15(17.5)KV XLPE cable(3 cores)	70-120	
8.7/15(17.5)KV RSNY/3-3		150-240	
8.7/15(17.5)KV RSNY/3-4		300-400	
8.7/15(17.5)KV RSWY/3-1		25-50	
8.7/15(17.5)KV RSWY/3-2	Outdoor termination for 8.7/15(17.5)KV XLPE cable(3 cored)	70-120	
8.7/15(17.5)KV RSWY/3-3	8.7/15(17.5)KV XLPE cable(3 cored)	150-240	
8.7/15(17.5)KV RSWY/3-4		300-400	
8.7/15(17.5)KV RSNZ/3-1		Indoor termination for 8.7/15KV(17.5)KV PILC cable(3 cores)	25-50
8.7/15(17.5)KV RSNZ/3-2		8.7/15KV(17.5)KV PILC cable(3 cores)	70-120
8.7/15(17.5)KV RSNZ/3-3	150-240		
8.7/15(17.5)KV RSNZ/3-4	300-400		
8.7/15(17.5)KV RSWZ/3-1	Outdoor termination for 8.7/15(17.5)KV PILC cable(3 cores)		25-50
8.7/15(17.5)KV RSWZ/3-2	8.7/15(17.5)KV PILC cable(3 cores)	70-120	
8.7/15(17.5)KV RSWZ/3-3		150-240	
8.7/15(17.5)KV RSWZ/3-4		300-400	

Aluminum or Copper Lug, Support insulator, Tee bracket can be supplied as specification.