

## 12/20(24)KV Heat Shrinkable Indoor/Outdoor Termination

**Usage:** XLPE cable

### Components:

Stress –control tubes, Insulation 3-way breakout, Insulation tubes, Sealing tubes, Filler mastic.

Stress relieving mastic, Sealing mastic, Silicone grease, Phase-color tubes, Rain shed, Cleaning tissue.

Soldering tin, Soldering unguent, Earth braid, Copper binding wire, Abrasive paper, Gloves.



### Order Reference:

Type/Order No	Name	Cable range(mm <sup>2</sup> )
12/20(24)KV RSNY/1-1	Indoor termination	25-50
12/20(24)KV RSNY/1-2	for 12/20(24)KV	70-120
12/20(24)KV RSNY/1-3	XLPE cable(1 core)	150-240
12/20(24)KV RSNY/1-4		300-400
12/20(24)KV RSWY/1-1	Outdoor termination	25-50
12/20(24)KV RSWY/1-2	for 12/20(24)KV	70-120
12/20(24)KV RSWY/1-3	XLPE cable(1core)	150-240
12/20(24)KV RSWY/1-4		300-400
12/20(24)KV RSNY/3-1	Indoor termination	25-50
12/20(24)KV RSNY/3-2	for 12/20(24)KV	70-120
12/20(24)KV RSNY/3-3	XLPE cable(3 cores)	150-240
12/20(24)KV RSNY/3-4		300-400
12/20(24)KV RSWY/3-1	Outdoor termination	25-50
12/20(24)KV RSWY/3-2	for 12/20(24)KV	70-120
12/20(24)KV RSWY/3-3	XLPE cable(3 cores)	150-240
12/20(24)KV RSWY/3-4		300-400

Aluminum or Copper Lug, Support insulator, Tee bracket can be supplied as specification

## 12/20(24)KV Heat Shrinkable Straight Through Joint

**Usage:** XLPE cable

Components: Stress-control tube, Insulating/Conductive tube, Inner-sleeve, Protective sleeve, Copper screen mesh, Semi-conductive tape, J-30 Tape, PVC tape, Sealing mastic, Stress relieving mastic, Silicon grease. Earth braid, Cleaning tissue, Copper binding wire, Soldering tin, Soldering unguent, Cotton strap. Gloves, Abrasive strap.

### Order Reference

Type/Order No	Name	Cable range(mm <sup>2</sup> )
12/20(24)KV RSJY/1-1	Straight termination	25-50
12/20(24)KV RSJY/1-2	for 12/20(24)KV	70-120
12/20(24)KV RSJY/1-3	XLPE cable	150-240
12/20(24)KV RSJY/1-4	(1 core)	300-400
12/20(24)KV RSJY/3-1	Straight termination	25-50
12/20(24)KV RSJY/2-2	for 12/20(24)KV	70-120
12/20(24)KV RSJY/3-3	XLPE cable	150-240
12/20(24)KV RSJY/3-4	(3 cores)	300-400

Aluminum or Copper Ferrule and Amour continue components can be supplied as specification