

FRY Heat Shrinkable Tubular Sleeve for Going Through Walls

- ◆Mainly applied to pipe joint corrosion protection , reducer and seal of valve. Its circle shrinkable ration \geq 50%
- ◆A high-performance heat sensitive adhesive effectively bonds to steel substrates and common pipeline coatings including polyethylene, polypropylene, fusion bonded epoxy and coal tar enamel to form a reliable seal protection
- ◆The sleeve have strong shrink power for their unitary structure. It has excellent properties of soil stress creep resistance
- ◆Long term corrosion protection



Product Dimensions:

Size	Suitable Dia of Pipeline	Size	Suitable Dia of Pipeline
FRYΦ30X250	DN15(Φ22)	FRYΦ80X350	DN50(Φ57)
FRYΦ30X300	DN15(Φ22)	FRYΦ80X450	DN50(Φ57)
FRYΦ30X350	DN15(Φ22)	FRYΦ120X350	DN65(Φ76)
FRYΦ30X450	DN15(Φ22)	FRYΦ120X450	DN65(Φ76)
FRYΦ50X350	DN25(Φ34)	FRYΦ120X500	DN65(Φ76)
FRYΦ50X450	DN25(Φ34)	FRYΦ120X350	DN80(Φ89)
FRYΦ60X350	DN32(Φ42)	FRYΦ120X450	DN80(Φ89)
FRYΦ60X350	DN40(Φ48)	FRYΦ120X500	DN80(Φ89)
FRYΦ60X450	DN40(Φ48)	FRYΦ160X500	DN100(Φ108,114)

Annotation: The above data is normal size. Product size will in accordance with customers' demand.